

asbestos essentials

Non-licensed tasks

This information will help employers and the self-employed to comply with the Control of Asbestos Regulations 2006.

It is also useful for trade union and employee safety representatives.

Asbestos fibres can cause lung cancer and lung diseases.

The sheet covers the points you need to follow to reduce exposure to an adequate level.

It can act as a risk assessment for asbestos if it matches what you plan to do.

Follow all the points, or use equally effective measures.

Only carry out this work if you are properly trained and have the right equipment.

Main points

- Asbestos fibres can kill.
- Keep exposures low using all the controls in this sheet.
- Also follow sheet a0 and equipment and method (em) sheets; see 'Essential information'.

Removing asbestoscontaining bituminous products

What this sheet covers

This sheet describes good practice when you need to remove asbestoscontaining bituminous products such as built-up roofing, gutter linings or damp-proof courses.

This sheet is not appropriate for work with metal cladding lined with asbestos-containing bitumen (eg 'Galbestos') - see sheet a22.

Preparing the work area

- Ensure safe access.
- Restrict access minimise the number of people present.
- Use tape and notices to warn others.
- Ensure adequate lighting.

Caution: For roofwork, check if the roof may be fragile.

Equipment

- 500-gauge polythene sheeting and duct tape;
- warning tape and notices;
- sharp knife;
- scraper;
- shovel;
- garden-type sprayer containing wetting agent;
- bucket of water and rags;
- asbestos waste container, eg labelled polythene sack;
- clear polythene sack;
- lockable skip for larger quantities of waste; and
- for roofwork, interlocking bucket-type rubble chute into the skip.





Built up bituminous roofing and bituminous asbestos fabric over a doorway



SAFETY CHECKLIST

- Can you avoid disturbing asbestos by doing the job in some other way?
- Do you need a licence for the work?
- Always follow all legal requirements.
- Follow the task guidance sheet.
- Use an asbestos waste container.
- Take asbestos waste to a licensed disposal site.

Caution:

- Don't sweep up dust or debris use a Class H vacuum cleaner or damp rags.
- Don't take used overalls home.
- Don't re-use disposable PPE.
- Don't smoke.
- Don't eat or drink in the work area.


OTHER HAZARDS

Work at height - see www.hse.gov.uk/falls/index.htm. Take precautions to avoid falls. Must you work from a ladder? Where necessary, erect an access platform.

Work on fragile roofs - see www.hse.gov.uk/construction/ information.htm. Fragile roofs cannot bear weight.

Manual handling - see www.hse.gov.uk/msd/index.htm. Plan how to remove and handle heavy material and articles safely.

There may also be other hazards - you need to consider them all.





Cut and remove maneagable sections

Personal protective equipment (PPE)

- Provide:
 - disposable overalls fitted with a hood; and
 - boots without laces (laced boots are hard to decontaminate).
- A respirator is not normally required.

Procedure

■ Seal access points, eg skylights, with polythene sheeting and duct tape.

Caution: It is dangerous to seal over exhaust vents from gas-fired equipment. Can the equipment be turned off?

Overlaying AC sheets

- Can you avoid removal, eg by overlaying with non-asbestos bituminous felt?
- Warn the building owner about the presence of asbestos material, so it can be managed properly.

Removal

- Can you minimise the amount for removal, cutting around the area?
- For safe handling, cut and remove manageable sections. Place these in the chute or the skip.
- Remove adhering material by dampening and gentle scraping.
- Collect up all debris.
- Remove large dust deposits by dampening and shovelling into the waste container.
- Dampen dust and debris from disintegrating felt and place in the waste container.
- Caution: Don't rip up asbestos bituminous felt; never burn the debris.

Cleaning and disposal

- Clean the equipment with damp rags.
- Dismantle and decontaminate the chute with damp rags.
- Put debris, used rags, polythene sheeting, and other waste in the asbestos waste container and tape it closed.
- Put the asbestos waste container in a clear polythene sack and tape it closed.
- Disposal see sheet em9.

Personal decontamination

■ See sheet em8



MORE HELP

- Licensed asbestos contractors, and training providers - HSE's Infoline Tel: 0845 345 0055 Textphone: 0845 408 9577 e-mail: hse.infoline@natbrit.com and at www.hse.gov.uk/asbestos/ licensing/index.htm
- HSE priced and free publications -HSE Books Tel: 01787 881165 and at www.hsebooks.co.uk
- Qualified hygienists The British Occupational Hygiene Society (BOHS) Tel: 01332 298101 and at www.bohs.org/ under 'Professional > Consultants'
- Trade associations the Asbestos Removal Contractors Association (ARCA) Tel: 01283 531126 Website: www.arcaweb.org.uk, or the Asbestos Control and Abatement Division (ACAD) Tel: 01325 466704
- Disposal of asbestos waste www.environment-agency.co.uk, www.sepa.org.uk/, or www.netregs.gov.uk/netregs.
- More asbestos pictures www.hse.gov.uk/asbestos/gallery.htm
- Help to decide if work is licensed www.hse.gov.uk/asbestos/licensing/ index.htm

Clearance and checking off

- Visually inspect the area to make sure that it has been cleaned properly.
- Clearance air sampling is not normally required.
- Get the premises owner, duty-holder or client to check off the job.

ESSENTIAL INFORMATION

Download and follow these advice sheets from www.hse.gov.uk /asbestos/essentials/index.htm:

em1 What to do if you uncover or damage materials that could contain asbestos

em2 Training

em5 Wetting asbestos materials

em7 Using damp rags to clean surfaces of minor asbestos contamination

em8 Personal decontamination

em9 Disposal of asbestos waste

a21

This document is available at www.hse.gov.uk/asbestos/essentials/index.htm

© Crown copyright This publication may be freely reproduced, except for advertising, endorsement or commercial purposes. First published as part of Asbestos Essentials Task Manual 2001. Please acknowledge the source as HSE.

Published by the Health and Safety Executive 12/07

This guidance is issued by the Health and Safety Executive. Following the guidance is not compulsory and you are free to take other action. But if you do follow the guidance you will normally be doing enough to comply with the law. Health and safety inspectors seek to secure compliance with the law and may refer to this guidance as illustrating good practice.